WAVESTREAM

SKYEDGE II-C CAPRICORN PLUS

High speed VSAT for multiple data intensive applications

ENABLING DATA INTENSIVE SERVICES

Today's growing need for data intensive applications requires higher-speed VSATs. Capricorn PLUS is designed with this need in mind, providing high throughput of up to 400Mbps download and 100Mbps upload concurrently. This enables multiple hundreds of users to simultaneously use popular media rich applications, seamlessly over a satellite link. Wavestream provides a unique and comprehensive solution for data intensive services that is achieved when combined with Wavestream's patented Dynamic Channels technology for full network utilization. Wavestream is paving the way to 5G backhauling over satellite with higher throughputs and greater efficiencies to support exponential growth in network capacity as well as in the number and types of connected devices and services.

SERVING MULTIPLE APPLICATIONS

Capricorn PLUS is a member of the SkyEdge II-c multi-application platform enabling a shared bandwidth pool for a wide variety of applications such as maritime, enterprise and 4G/5G cellular backhaul with backward compatibility to 2G/3G networks. These use cases have a significantly different traffic profile which traditionally required separate bandwidth pools for each application, causing an inefficient use of bandwidth due to a static resources allocation. Wavestream's field-proven Dynamic Channels technology enables optimal dynamic allocation of bandwidth every 40 msec, truly adapting the network resources to each application's need on a per VSAT basis, according to the required SLA.

BUILT FOR GLOBAL MOBILITY NETWORKS

Capricorn PLUS has added value stemming from SkyEdge II-c's scalability and flexibility for large global mobility networks that supports tens of satellites and teleports and practically an unlimited number of VSATs over a single network. This network is managed by Wavestream's advanced, field proven, TotalNMS providing a comprehensive management suite for the mobility network operator as well as their VNOs. Moreover, SkyEdge II-c Cloud QoS enables SLA enforcement over multiple satellites and beams per VNO or group of VSATs. Capricorn PLUS Mobility services include: high-speed Doppler compensation, transmit power control with link adaptation, OpenAMIP antenna interface and dynamic spread spectrum and PSD control. The VSAT also incorporates Automatic Beam Switchover (ABS), ensuring continuity of passenger service. ABS is managed via Wavestream's sophisticated centralized mobility manager ensuring optimal beam switching decisions according to location, load, SLA and regulation.



BENEFITS

- More Services for data intensive applications such as backhaul 4G/5G, maritime, enterprise
- More Throughput up to 400/100Mbps for data intensive applications
- More Virtualization with Multi access Edge Computing (MEC) infrastructure
- More Compatibility to 5G architecture
- More Efficiency less satellite capacity for more sites with more throughput
- More Adaptivity full resource utilization under any link conditions and service needs
- More Security supporting latest authentication and encryption protocols
- More Integration Simplicity via multiple protocol acceleration over Layer-2 and Layer-3 topologies



COMPLETE FEATURE SET

Capricorn PLUS is a Multi access Edge Computing (MEC) enabled IP router supporting value-added virtualized functions and includes all the SkyEdge II-c VSAT platform features, such as advanced application-based QoS, VLANs, and next generation IPv6 networking. Capricorn PLUS can also be configured as a Layer-2 modem enabling seamless integration to the cellular core, Telco and Enterprise networks. This simple core network integration at Layer-2 or Layer-3 ensures the required operational flexibility for any type of service provisioning.

To ensure fast web browsing and a high-quality user experience for a variety of applications, Capricorn PLUS contains a full set of protocol optimization and application acceleration for both Layer3 and Layer2 network topologies.

Capricorn PLUS provides the highest level of transmission security, supporting X.509 terminal authentication, and AES-256 link layer encryption with dynamic key rotation to protect all user traffic.

MAXIMUM SPECTRAL EFFICIENCY

- 802.1g and 802.1ad for

Point to Point, Point to

IPv4/IPv6, TCP, UDP, ICMP,

RTP header compression,

IGMPv2/v3. SIP. VRFs.

RIPv2, Static Routes

ENHANCED FEATURES

Doppler compensation,

interface. PSD control.

Cellular - 4G:

Volte

Security:

CMPv2

automatic satellite/beam

Geo fencing, No Tx zones

switching, OpenAMIP antenna

GTP (IPv6/IPv4) acceleration,

AES-256 bit link encryption

IPsec Client, ACL Firewall.

Certificate Enrollment with

X.509 Terminal Authentication.

- VLANs support

DHCP, NAT/PAT, DNS Caching,

UNI/NNI

Laver 3:

Other:

Mobility:

Multi-Point

Wavestream's innovative transmission technologies delivers exceptional performance and space segment efficiencies.

High availability and maximum bandwidth efficiency at any condition and for any number of VSATs for multiple concurrent applications is achieved with Wavestream's technology. Wideband DVB-S2X carriers in the forward direction and fast adaptive transmission with Wavestream's patented Dynamic Channels technology, powered with advanced LDPC codes in the return direction

This is achieved by adaptive power control, changes to the carrier symbol rate, modulation, coding and spread-spectrum factor per VSAT on a per time-slot basis, yielding full utilization of space segment while maximizing user-experience. Capricorn PLUS incorporates SDR technology enabling simple software upgrades enhancing the return channel capabilities even further.

TECHNICAL SPECIFICATIONS

FORWARD CHANNEL

Standard: DVB-S2X ACM Carrier Channel: 1.5Msps-500Msps Modulation: QPSK, 8PSK, 16APSK, 32APSK, 64APSK, 256APSK Coding: LDPC, BCH all DVB-S2X FEC rates

RETURN CHANNEL

Access Scheme: MF-TDMA Dynamic Channels

Carrier Channel: 128Ksps – 30Msps

(Future – 50Msps) Modulation:

16QAM, QPSK, BPSK, S-BPSK (up to 12 SF)

Coding: LDPC (Future – XDC)

PERFORMANCE FWD: 400Mbps RTN:

100Mbps

MODEM INTERFACES

RF Input / Output:

- 2 female F-connectors, 75Ω,
- RF in: 950-2150MHz
- RF out: 950-24 00MHz DISEqC **Data Interfaces:**
- 2 x Ethernet 10 GbE RJ-45 , Auto negotiation
- 1 x Ethernet 10/100/1000BaseT RJ-45 1 x Serial Interface RJ-45
- Management Interface:
- 4 x Ethernet
- 10/100/1000BaseT RJ-45 - Web-based local management
- SNMP

NETWORKING

- Layer 2:
- Layer 2 Ethernet frame forwarding, VLAN Re-tagging
- ABOUT WAVESTREAM

Wavestream sets the standard in the design and manufacture of next generation high power solid state amplifiers. Wavestream's Family of Ka, Ku and X-band Solid State Power Amplifiers (SSPAs), Block Upconverters (BUCs) and transceivers provide systems integrators with field-proven, high performance solutions designed for ground mobile and fixed, gateway and airborne satellite communication systems worldwide.

These items are subject to the Export Administration Regulations (EAR), 15 C.F.R. Parts 730-774, and may not be exported or transferred to any non-U.S. person, except as authorized by the U. S. Department of Commerce.

All registered trademarks are the property of their respective companies. This brochure is being provided for informational purposes only. The details contained in this document, including product and feature specifications, are subject to change without notice and shall not bind Wavestream to a specific product or set of features related thereto. DVB is a registered trademark of the DVB Project.

QoS:

Per VSAT and per VNO: CIR, MIR, CBR, DiffServ support, strict and weighted priority based queuing, 802.1p – priority based QoS (for layer 2)

Cloud-QoS

Global QoS management over multiple satellite and/or beams, on a per Managed Group basis

ENVIRONMENTAL AND MECHANICAL

Operating Voltage: - 48V DC Operating Temperature:

0°C to +50°C Certifications: CE, FCC, EMC

OUTDOOR UNIT (ODU)

Frequency Bands: C, Ku, Ka Transmit Power: Via IDU 24V or 48V DC insertion up to 12W BUC Antenna / BUC Size:

Variable **Operating Temperature:** -40°C to +60°C

CONTACT US

- 545 West Terrace Drive San Dimas, California 91773 USA
- T. +1 909 599 9080
- F. +1 909 599 9082
- www.wavestream.com

sales@wavestream.com

